



LAND CORNER RECORD

Index: S-14	Corner: NW1/16	State of Indiana - Hoosier National Forest		
Section: 27	Township: 7N	Range: 1E	P.M.: 2nd	County: Monroe
Coordinate:	Lat./N: 1373053.928	Long./E: 3146538.713	Datum: NAD83 IN West Zone, US Survey Feet	

CORNER HISTORY: (Chronological history of corner)					
1.) Date of Survey:	Surveyor:	Monument:	Recording Information:		Monument Photograph:
10/4/1982	Ken Anderson L.S. #80040545	PK nail set	USDA Forest Service Bedford, IN		
Reference Objects:	Species:	Diameter:	Bearing:	Distance:	
Record evidence of prior survey:					
2.) Date of Survey:	Surveyor:	Monument:	Recording Information:		
Reference Objects:	Species:	Diameter:	Bearing:	Distance:	
Record evidence of prior survey:					

ACCESSORIES: Bearing and distance from monument to witness object.				
Reference Objects:	Object or Tree Species:	Diameter:	Bearing:	Distance:
	Red Oak	13"	N77°W	90.96'
	Monument (R14.05-.96)	N/A	N70°E	83.30'
	Monument (S14-.1)	N/A	S05°W	131.74'
Monument Found or Set:	A mag nail with a washer stamped "BRCJ IN 6892 IN" set 0.1' below grade.			

MONUMENT SKETCH	NARRATIVE REFERENCE:
	Monument is a mag nail with a washer stamped "BRCJ INC 6892 IN" set 0.1' below grade, located 8' west of the edge of asphalt of State Road 446, 2' east of the white paint stripe, 25' west of a north-south running ditch line that is running parallel with 446, 65' south of a Forestry entrance, 300' north of Tower Ridge Road, 15' east of the centerline of the highway.

SECTION DIAGRAM	PERPETUATION RECORD:
 Corner Location = ●	The monument was set and maintained by establishing one new bearing tree and two new reference objects. One new bearing tree was marked with a blaze, scribed B.T., bearing tree sign, paint, and mag nail. <i>Referenced on BRCJ survey recorded as InstNo.2018007752</i> <i>Accepted by the Monroe County Surveyor Review Board on August 6, 2019.</i>
Section: 27 T7N R1E	Prepared By: BRCJ (Project#3-0822) Date: 5/2018